

29 申請建築物總樓面面積寬免的資料

INFORMATION IN APPLICATION FOR CONCESSION ON GROSS FLOOR AREA (GFA) OF BUILDING

獲寬免總樓面面積的設施分項

於印製售樓說明書前呈交予並已獲建築事務監督批准的一般建築圖則上有關總樓面面積寬免的分項的最新資料，請見下表。如印製售樓說明書時尚未呈交最終修訂圖則予建築事務監督，則有(＃)號的資料可以由認可人士提供的資料作為基礎。直至最終修訂圖則於發出佔用許可證前呈交予並獲建築事務監督批准前，以下分項資料仍可能有所修改。

根據《建築物(規劃)規例》第23(3)(b)條不計算的總樓面面積		面積(平方米)
1.(#)	停車場及上落客貨地方(公共交通總站除外)	2049.752
2.	機房及相類設施	
2.1	所佔面積受相關《認可人士、註冊結構工程師及註冊岩土工程師作業備考》(《作業備考》)或規例限制的強制性設施或必要機房，例如升降機機房、電訊及廣播設備室、垃圾及物料回收房等	196.207
2.2(#)	所佔面積不受任何《作業備考》或規例限制的強制性設施或必要機房，例如僅由消防裝置及設備佔用的房間、電錶房、電力變壓房、食水及鹹水缸等	770.331
2.3	非強制性或非必要機房，例如空調機房、送風櫃房等	75.022
根據聯合作業備考第1及第2號提供的環保設施		面積(平方米)
3.	露台	330.794
4.	加闊的公用走廊及升降機大堂	不適用
5.	公用空中花園	不適用
6.	隔聲鰭	不適用
7.	翼牆、捕風器及風斗	不適用
8.	非結構預製外牆	不適用
9.	工作平台	181.500
10.	隔音屏障	不適用

註：上述表格是根據屋宇署所發出的《認可人士、註冊結構工程師及註冊岩土工程師作業備考》ADM-2規定的要求而制訂的。屋宇署會按實際需要不時更改有關要求。

適意設施		面積(平方米)
11.	管理員宿舍、供保安人員和管理處員工使用的櫃位、辦事處、貯物室、警衛室和廁所，以及業主立案法團辦事處	不適用
12.	住戶康樂設施，包括僅供康樂設施使用的中空空間、機房、游泳池的濾水機房、有蓋人行道等	360.845
13.	有蓋園景區及遊樂場地	408.650
14.	橫向屏障 / 有蓋人行道及花棚	不適用
15.	擴大升降機槽	65.301
16.	煙囪管道	不適用
17.	其他非強制性或非必要機房，例如鍋爐房、衛星電視共用天線房	不適用
18.(#)	強制性設施或必要機房所需的管槽及氣槽	78.131
19.	非強制性設施或非必要機房所需的管槽及氣槽	26.096
20.	環保系統及設施所需的機房、管槽及氣槽	不適用
21.	複式住宅單位及洋房的中空空間	不適用
22.	遮陽篷及反光罩	不適用
23.(#)	小型伸出物，例如空調機箱、空調機平台、窗檻及伸出的窗台	不適用
24.	《作業備考》APP-19第3(b)及(c)段沒有涵蓋的其他伸出物，如空調機箱及空調機平台	不適用
其他項目		面積(平方米)
25.(#)	庇護層，包括庇護層兼空中花園	不適用
26.	大型伸出 / 外懸設施下的有蓋地方	不適用
27.	公共交通總站	不適用
28.(#)	共用構築物及公用樓梯	不適用
29.(#)	僅供獲接納不計入總樓面面積的樓層使用的樓梯、升降機槽及垂直管道的水平面積	290.056
30.	公眾通道	不適用
31.	有蓋的後移部分	不適用
額外總樓面面積		面積(平方米)
32.	額外總樓面面積	207.260
根據聯合作業備考(第8號)提供的額外環保設施		面積(平方米)
33.	採用「組裝合成」建築法的樓宇	不適用

29 申請建築物總樓面面積寬免的資料

INFORMATION IN APPLICATION FOR CONCESSION ON GROSS FLOOR AREA (GFA) OF BUILDING

有關建築物的環境評估



期數的公用部分的預計能量表現或消耗

於印製售樓說明書前呈交予建築事務監督有關期數的公用部分的預計能量表現或消耗的最近期資料：

第 I 部分						
提供中央空調		是				
提供具能源效益的設施		是				
擬安裝的具能源效益的設施		(1)設計建築物方向以減少太陽熱能吸收 (2)高能源效益的空調系統 (3)降低窗牆比例				
第 II 部分：擬興建樓宇/部分樓宇之預計每年能源消耗量 ^(註腳1)						
發展項目類型	位置	使用有關裝置的內部樓面面積 (平方米)	基線樓宇 ^(註腳2) 每年能源消耗量		擬興建樓宇每年能源消耗量	
			電力 千瓦小時 / 平方米 / 年	煤氣 / 石油氣 用量單位 / 平方米 / 年	電力 千瓦小時 / 平方米 / 年	煤氣 / 石油氣 用量單位 / 平方米 / 年
住用發展項目 (不包括酒店)	有使用中央屋宇裝備裝置 ^(註腳3) 的部分	6,464	290.89	85.28	215.69	47.58
非住用發展項目 (包括酒店) ^(註腳4)	平台 (非中央屋宇裝備置)	1,633	340.40	不適用	320.60	不適用
第 III 部分：以下裝置乃按機電工程署公布的相關實務守則設計						
照明裝置		是	升降機及自動梯的裝置		是	
空調裝置		是	以總能源為本的方法		不適用	
電力裝置		是				

- 註腳： 1. 一般而言，一棟樓宇的預計“每年能源消耗量”愈低，其節約能源的效益愈高。如一棟樓宇預計的“每年能源消耗量”低於該樓宇的“基線樓宇每年能源消耗量”，則代表預計該樓宇的能源應用較其基線樓宇有效，削減幅度愈大則代表有關樓宇能源節約的效益愈高。預計每年能源消耗量〔以耗電量(千瓦小時/平方米/年)及煤氣 / 石油氣消耗量(用量單位/平方米/年)計算〕，指將發展項目的每年能源消耗總量除以使用有關裝置的內部樓面面積所得出的商，其中：-
- (a) “每年能源消耗量”與新建樓宇BEAM Plus 標準(現行版本)中的「年能源消耗」具有相同涵義；及
- (b) 樓宇、空間或單位的“內部樓面面積”，指外牆及 / 或共用牆的內壁之內表面起量度出來的樓面面積。
2. “基線樓宇”與新建樓宇BEAM Plus 標準(現行版本)中的“基準建築物模式(零分標準)”具有相同涵義。
3. “中央屋宇裝備裝置”與機電工程署發出的《屋宇裝備裝置能源效益實務守則》中的涵義相同。
4. 平台一般指發展項目的最低部分(通常為發展項目最低15米部分及其地庫(如適用))，並與其上的塔樓具有不同用途。對於並無明確劃分平台與塔樓的發展項目，應視整個發展項目為塔樓。

29 申請建築物總樓面面積寬免的資料

INFORMATION IN APPLICATION FOR CONCESSION ON GROSS FLOOR AREA (GFA) OF BUILDING

Breakdown of GFA Concessions Obtained for All Features

Latest information on breakdown of GFA concessions as shown on the general building plans submitted to and approved by the Building Authority (BA) prior to the printing of the sales brochure is tabulated below. Information marked (#) may be based on information provided by the authorized person if the sales brochure is printed prior to submission of the final amendment plans to the BA. The breakdown of GFA concessions may be subject to further changes until final amendment plans are submitted to and approved by the BA prior to the issuance of the occupation permit for the development.

Disregarded GFA under Building (Planning) Regulations 23(3)(b)		Area (m ²)
1.(#)	Carpark and loading / unloading area excluding public transport terminus	2049.752
2.	Plant rooms and similar services	
2.1	Mandatory feature or essential plant room, area of which is limited by respective Practice Notes for Authorized Persons, Registered Structural Engineers and Registered Geotechnical Engineers (PNAP) or regulation such as lift machine room, telecommunications and broadcasting (TBE) room, refuse storage and material recovery chamber, etc.	196.207
2.2(#)	Mandatory feature or essential plant room, area of which is NOT limited by any PNAP or regulation such as room occupied solely by fire services installations (FSI) and equipment, meter room, transformer room, potable and flushing water tank, etc.	770.331
2.3	Non-mandatory or non-essential plant room such as air-conditioning (A/C) plant room, air handling unit (AHU) room, etc.	75.022
Green Features under Joint Practice Notes 1 and 2		Area (m ²)
3.	Balcony	330.794
4.	Wider common corridor and lift lobby	Not applicable
5.	Communal sky garden	Not applicable
6.	Acoustic fin	Not applicable
7.	Wing wall, wind catcher and funnel	Not applicable
8.	Non-structural prefabricated external wall	Not applicable
9.	Utility platform	181.500
10.	Noise barrier	Not applicable

Note: The above table is based on the requirements as stipulated in the Practice Note for Authorized Persons, Registered Structural Engineers and Registered Geotechnical Engineers ADM-2 issued by the Buildings Department. The Buildings Department may revise such requirements from time to time as appropriate.

Amenity Features		Area (m ²)
11.	Caretaker's quarters, counter, office, store, guard room and lavatory for watchman and management staff and owners' corporation office	Not applicable
12.	Residential recreational facilities including void, plant room, swimming pool filtration plant room, covered walkway, etc. serving solely the recreational facilities	360.845
13.	Covered landscaped and play area	408.650
14.	Horizontal screen/covered walkway and trellis	Not applicable
15.	Larger lift shaft	65.301
16.	Chimney shaft	Not applicable
17.	Other non-mandatory or non-essential plant room, such as boiler room, satellite master antenna television (SMATV) room	Not applicable
18.(#)	Pipe duct, air duct for mandatory feature or essential plant room	78.131
19.	Pipe duct, air duct for non-mandatory or non-essential plant room	26.096
20.	Plant room, pipe duct, air duct for environmentally friendly system and feature	Not applicable
21.	Void in duplex domestic flat and house	Not applicable
22.	Sunshade and reflector	Not applicable
23.(#)	Minor projection such as A/C box, A/C platform, window cill and projecting window	Not applicable
24.	Other projection such as A/C box and platform not covered in paragraph 3(b) and (c) of PNAP APP-19	Not applicable
Other Exempted Items		Area (m ²)
25.(#)	Refuge floor including refuge floor cum sky garden	Not applicable
26.	Covered area under large projecting/ overhanging feature	Not applicable
27.	Public transport terminus	Not applicable
28.(#)	Party structure and common staircase	Not applicable
29.(#)	Horizontal area of staircase, lift shaft and vertical duct solely serving floor accepted as not being accountable for GFA	290.056
30.	Public passage	Not applicable
31.	Covered set back area	Not applicable
Bonus GFA		Area (m ²)
32.	Bonus GFA	207.260
Additional Green Features under Joint Practice Note (No. 8)		Area (m ²)
33.	Buildings adopting Modular Integrated Construction	Not applicable

29 申請建築物總樓面面積寬免的資料

INFORMATION IN APPLICATION FOR CONCESSION ON GROSS FLOOR AREA (GFA) OF BUILDING

The Environmental Assessment of the Building



Estimated Energy Performance or Consumption for the Common Parts of the Phase

Latest information on the estimated energy performance or consumption for the common parts of the Phase as submitted to the Building Authority prior to the printing of the sales brochure:

Part I						
Provision of Central Air Conditioning			Yes			
Provision of Energy Efficient Features			Yes			
Energy Efficient Features proposed			(1) Design building orientation for reducing solar heat gain (2) Select more energy-efficient air-conditioning units (3) Reduce the window-to-wall ratio			
Part II: The predicted annual energy use of the proposed building / part of building ^(Note 1)						
Type of Development	Location	Internal Floor Area Served (m²)	Annual Energy Use of Baseline Building ^(Note 2)		Annual Energy Use of Proposed Building	
			Electricity kWh / m² / annum	Town Gas / LPG unit / m² / annum	Electricity kWh / m² / annum	Town Gas / LPG unit / m² / annum
Domestic Development (excluding Hotel)	Area served by central building services installation ^(Note 3)	6,464	290.89	85.28	215.69	47.58
Non-domestic Development (including Hotel) ^(Note 4)	Podium(s) (non-central building services installation)	1,633	340.40	Not applicable	320.60	Not applicable
Part III : The following installations are designed in accordance with the relevant Codes of Practices published by the Electrical & Mechanical Services Department (EMSD)						
Lighting Installations	Yes		Lift & Escalator Installations		Yes	
Air Conditioning Installations	Yes		Performance-based Approach		Not Applicable	
Electrical Installations	Yes					

- Notes: 1. In general, the lower the estimated “Annual Energy Use” of the building, the more efficient the building in terms of energy use. For example, if the estimated “annual energy use of proposed building” is less than the estimated “annual energy use of baseline building”, it means the predicted use of energy is more efficient in the proposed building than in the baseline building. The larger the reduction, the greater the efficiency. The predicted annual energy use, in terms of electricity consumption (kWh/m²/annum) and town gas/LPG consumption (unit/m²/annum), of the development by the internal floor area served, where: –
- (a) “total annual energy use” has the same meaning of “annual energy use” in the BEAM Plus New Buildings (current version); and
- (b) “internal floor area”, in relation to a building, a space or a unit means the floor area of all enclosed space measured to the internal faces of enclosing external and/or party walls.
2. “Baseline Building” has the same meaning as “Baseline Building Model (zero-credit benchmark)” in the BEAM Plus New Buildings (current version).
3. “Central Building Services Installation” has the same meaning as that in the Code of Practice for Energy Efficiency of Building Services Installation issued by the Electrical and Mechanical Services Department.
4. Podium(s) normally means the lowest part of the development (usually the lowest 15m of the development and its basement, if any) carrying different use(s) from that of the tower(s) above. For development without clear demarcation between podium(s) and tower(s), the development, as a whole, should be considered as tower(s).