

## 4. 發展項目的設計的資料 INFORMATION ON DESIGN OF THE DEVELOPMENT

發展項目有構成圍封牆的一部分的非結構預製外牆。每幢建築物的非結構預製外牆的厚度範圍為150毫米。  
There are non-structural prefabricated external walls forming part of the enclosing walls of the development.  
The range of thickness of the non-structural prefabricated external walls of the building is 150mm.

發展項目有構成圍封牆的一部分的幕牆。每幢建築物的幕牆厚度範圍為200毫米。  
There are curtain walls forming part of the enclosing walls of the development.  
The range of thickness of the curtain walls of the building is 200mm.

### 每個住宅物業的非結構的預製外牆及幕牆的總面積

#### Schedule of total area of the non-structural prefabricated external walls and curtain walls of each residential property

樓層 Floor	單位 Flat	每個住宅物業的非結構的預製外牆的總面積 (平方米) Total area of the non-structural prefabricated external walls of each residential property (sq.m.)	每個住宅物業的幕牆的總面積 (平方米) Total area of the curtain walls of each residential property (sq.m.)
3/F	A	-	-
	B	-	0.195
	C	-	0.275
	D	-	0.275
	E	0.191	0.275
	F	0.387	0.543
	G	0.025	0.275
	H	-	0.195
	J	-	-
	K	-	0.275
	L	-	0.275
	M	-	-
	N	-	-
	P	0.216	0.880
Q	0.353	0.910	
5/F - 12/F, 15/F - 23/F, 25/F - 33/F, 35/F - 36/F	R	-	0.265
	A	-	0.430
	B	-	0.485
	C	-	0.565
	D	-	0.530
	E	0.182	0.530
	F	0.501	0.893
	G	0.025	0.565
	H	-	0.485
	J	-	0.430
	K	-	0.565
	L	-	0.565
	M	-	0.440
	N	-	0.440
P	0.225	1.210	
Q	0.344	0.910	
R	-	0.755	

備註：在本售樓說明書中，“Unit”及“Flat”（當提及住宅物業時）這兩個詞彙可能是互換使用。

Note: In this sales brochure, the terms “Unit” and “Flat” (when referring to a residential property) may be used interchangeably.